

UNDER DEVELOPMENT

ARM7TDMI Processor Functional Description

This hardware component is a ARM7TDMI processor core. This is only an ISS, which should be wrapped with an [IssWrapper](#).

The simulation model is actually an instruction set simulator with an ARM7TDMI pipeline.

Currently it only exists in bigendian form.

Component definition

Available in source:trunk/soclib/soclib/lib/arm7tdmi/metadata/arm7tdmi.sd

Usage

ARM7TDMI has no parameters.

```
Uses('iss_wrapper', iss_t = 'common:arm7tdmi')
```

Before compiling any SoClib simulator using the ARM7TDMI you will need to download the UNISIM ([\[http://www.unisim.org\]](http://www.unisim.org)) library. To do so just download it using svn from [?https://unisim.org/svn/devel/unisim_lib](https://unisim.org/svn/devel/unisim_lib) with the following command:

```
svn import ?https://unisim.org/svn/devel/unisim_lib
```

You will have to enter a username and password. If you do not have access to the UNISIM development, you can simply use 'guest'/'guest' for username and password respectively.

ARM7TDMI Processor ISS Implementation

The implementation is in

- source:trunk/soclib/lib/arm7tdmi/include/iss/arm7tdmi.h
- source:trunk/soclib/lib/arm7tdmi/src/iss/arm7tdmi.cpp

The previous files use the ARM7TDMI implementation provided in the UNISIM library.

Template parameters

This component has no template parameters.

Constructor parameters

```
MipsElIss(  
    sc_module_name name,    // Instance Name  
    int ident);             // processor id
```

or

```
MipsEbIss( name, ident);
```

Visible registers

The following internal registers define the processor internal state, and can be inspected:

- r_pc : Program counter
- m_ins : Instruction register
- r_gpr[i] : General registers ($0 < i < 32$)
- r_hi & r_lo : Intermediate registers for multiply / divide instructions
- r_cp0[i] : Coprocessor 0 registers ($0 \leq i < 32$). Implemented values:
 - ◆ 8: BAR : Bad address register
 - ◆ 12: SR : Status register
 - ◆ 13: CR : Cause register
 - ◆ 14: EPC : Exception PC register
 - ◆ 15: INFOS : CPU identification number on bits [9:0]

Interrupts

Mips defines 6 interrupts lines. ~~Le lowest number has the hiest priority.~~ The handling and prioritization of the interrupts is deferred to software.

Ports

None, it is to the wrapper to provide them.