

HalfGatewayInitiator

1) Functional Description

This hardware component is a subcomponent of RingGateway. It handles outgoing commands and incoming responses to and from the ring to which it is attached.

2) Component definition & usage

source:trunk/soclib/soclib/module/network_component/half_gateway_initiator/caba/metadata/half_gateway_initiator.sd

3) CABA implementation

CABA sources

- interface :
source:trunk/soclib/soclib/module/network_component/half_gateway_initiator/caba/source/include/half_gateway_initiator.h
- implementation :
source:trunk/soclib/soclib/module/network_component/half_gateway_initiator/caba/source/src/half_gateway_initiator.c

CABA Constructor parameters

```
HalfGatewayInitiator(sc_module_name      insname,           // instance name
                    bool                 alloc_init,         // default initiator token owner
                    const int             &rsp_fifo_depth,  // response fifo depth
                    const soclib::common::MappingTable &mt,  // mapping table
                    const soclib::common::IntTab &ringid,    // global subsystem index
                    bool local);                             // routing parameter
```

CABA ports

- sc_in<bool> p_clk; *Global system clock*
- sc_in<bool> p_resetn; *Global system reset*
- soclib::caba::RingIn p_ring_in; *Ring input port*
- soclib::caba::RingOut p_ring_out; *Ring output port*
- soclib::caba::GateInitiator p_gate_initiator; *Port to gate target*

4) TLMT implementation

The TLM-T implementation is not available yet.