

Processor Functional Description

This component is an ISS (Instruction Set Simulator), which can be wrapped in a CABA or TLM-T Wrapper.

It implements all instructions defined in the MIPS32 architecture specification, with the following limitations:

- The floating point instructions are not supported
- The Mips virtual memory instructions are not supported. The MMU is implemented as an external TLB (SoCLib generic MMU) in the VciVcacheWrapper? component.

Both little-endian and big-endian implementations are available.

Component definition & implementation

- source:trunk/soclib/soclib/lib/mips32/metadata/mips32.sd
- source:trunk/soclib/soclib/lib/mips32/include/mips32.h
- source:trunk/soclib/soclib/lib/mips32/src/mips32.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_cp0.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_hazard.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_instructions.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_load_store.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_run.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_special.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_special2.cpp
- source:trunk/soclib/soclib/lib/mips32/src/mips32_special3.cpp

Template parameters

This component has no template parameters.

Interrupts

Mips defines 6 interrupts lines. The handling and prioritization of the interrupts is deferred to software.

Ports

None, it is to the wrapper to provide them.