

NiosII Processor Functional Description

This hardware component belongs to the NiosII embedded processor family designed for Altera® field programmable gate array (FPGA) devices. The NiosII processor is a configurable soft-core processor, as opposed to a fixed, off-the-shelf processor. ?Configurable? means that features can be added or removed on a system-by-system basis to meet performance goals. Altera® offers three NiosII cores:

- NiosII/f. The NiosII/f ?fast? core is designed for fast performance.
- NiosII/s. The NiosII/s ?standard? core is designed for small size while maintaining performance.
- NiosII/e. The NiosII/e ?economy? core is designed to achieve the smallest possible core size.

This hardware component is only an ISS, which should be wrapped with an [IssWrapper](#).

The simulation model is actually an instruction set simulator, organized as a three-stage pipeline:

- First stage: instruction fetch, with access to the external instruction cache.
- Second stage: instruction is executed with a possible access to the external data cache.
- Third stage: read memory access is written back to registers

This component models the NiosII/f ?fast? core. Its main functional specifications are the following:

- Hardware multiplication and division are supported
- Floating-point instructions are supported by the way of custom instructions
- dynamic branch prediction is not supported
- optional tightly-coupled memory for instructions and data is not supported
- Load and store I/O instructions are not supported

Component definition

Available in source:trunk/soclib/soclib/iss/nios2_fast/metadata/nios2_fast.sd

Usage

NiosII has no parameters.

```
Uses ( 'nios2_fast' )
```

NiosII Processor ISS Implementation

The implementation is in

- source:trunk/soclib/soclib/iss/nios2_fast/include/iss/nios2_fast.h
- source:trunk/soclib/soclib/iss/nios2_fast/src/iss/nios2_fast.cpp
- source:trunk/soclib/soclib/iss/nios2_fast/src/iss/nios2_fast_itype_instructions.cpp
- source:trunk/soclib/soclib/iss/nios2_fast/src/iss/nios2_fast_rtype_instructions.cpp
- source:trunk/soclib/soclib/iss/nios2_fast/src/iss/nios2_fast_custom_instructions.cpp

Template parameters

This component has no template parameters.

Constructor parameters

```
Nios2fIss(  
    sc_module_name name,    // Instance Name  
    int ident);             // processor id
```

Visible registers

The following internal registers define the processor internal state, and can be inspected:

- `r_pc` : Program counter
- `m_instruction` : Instruction register
- `r_gpr[i]` : General-purpose registers ($0 < i < 32$)
- `r_ctr[i]` : Control registers ($0 < i < 6$)

Interrupts

NiosII defines 32 interrupt-request inputs. The lowest number has the highest priority.

Ports

None, it is to the wrapper to provide them.