VciLocks

1) Functional Description

This VCI target is a locks controller: In VCI-based systems, it is not anymore possible to "lock the bus" to implement the atomic *test & set* instructions used for software synchronisation. Therefore, this memory mapped hardware peripheral implements a set of binary locks:

- Each binary lock is a single flip-flop, but corresponds to 4 bytes in the address space. The segment allocated to this component must be aligned on a 4 bytes boundary. The number of available locks is defined by segment size / 4.
- Any read request is interpreted as a *test & set* operation: the value stored in the addressed flip-flop is returned, and the addressed flip-flop is set to 1.
- All write request are interpreted as *reset*: the addressed flip-flop is reset to 0.

This way, a spin lock is implemented as a simple loop waiting to read 0, and the lock release is a simple write operation. This components checks addresses for segmentation violation, and can be used as default target.

2) Component definition & usage

source:trunk/soclib/soclib/module/internal component/vci locks/caba/metadata/vci locks.sd?

```
Uses( 'vci_locks' )
```

3) CABA Implementation

CABA sources

• interface:

source:trunk/soclib/soclib/module/internal component/vci locks/caba/source/include/vci locks.h?

• implementation :

source:trunk/soclib/soclib/module/internal component/vci locks/caba/source/src/vci locks.cpp?

CABA Constructor parameters

CABA Ports

• sc_in<bool> p_resetn : Global system reset

• sc_in<bool> p_clk : Global system clock

• soclib::caba::VciTarget<vci_param> p_vci : The VCI port

VciLocks 1

4) TLM-DT implementation

TLM-DT sources

- interface:
 - source:trunk/soclib/soclib/module/internal component/vci locks/tlmdt/source/include/vci locks.h?
- implementation : source:trunk/soclib/soclib/module/internal_component/vci_locks/tlmdt/source/src/vci_locks.cpp?

TLM-DT Constructor parameters

TLM-DT Ports

• **p_vci** : VCI target port