

VciLocks Functional Description

SOCLIB COMPONENTS INDEX?



This VCI target is a locks controller : In VCI-based systems, it is not anymore possible to "lock the bus" to implement the atomic *test & set* instructions used for software synchronisation. Therefore, this memory mapped hardware peripheral implements a set of binary locks:

- Each binary lock is a single flip-flop, but corresponds to 4 bytes in the address space. The segment allocated to this component must be aligned on a 4 bytes boundary.
- Any read request is interpreted as a *test an set* operation : the value stored in the addressed flip-flop is returned, and the addressed flip-flop is set to 1.
- All write request are interpreted as *reset* : the the addressed flip-flop is reset to 0.

This way, a spin lock is implemented as a simple loop waiting to read 0, and the lock release is a simple write operation. This components checks addresses for segmentation violation, and can be used as default target.

VciLocks CABA Implementation

The caba implementation is in

- source:trunk/soclib/systemc/include/caba/target/vci_locks.h
- source:trunk/soclib/systemc/src/caba/target/vci_locks.cc

Template parameters:

- The VCI parameters

Constructor parameters

```
VciLocks(  
    sc_module_name name,    // Instance name  
    const soclib::common::IntTab &index,    // Target index  
    const soclib::common::MappingTable &mt);    // Mapping Table
```

Ports

- sc_in<bool> **p_resetn** : Global system reset
- sc_in<bool> **p_clk** : Global system clock
- soclib::common::VciiTarget<vci_param> **p_vci** : The VCI port