

VciMultiAhci

1) Functional Description

This component emulates a multi-channels disk controller with VCI interface. Each channel[k] can access a different physical disk, modeled as a different file[k] belonging to the host system, and containing a complete disk image. Each channel[k] can perform data transfers between file[k] and a buffer in the physical memory of the virtual system. The number of supported channels, the file name(s), the VCI burst size, and the block size are hardware parameters, defined as constructors parameters. The number of channels cannot be larger than 8. The burst size must be a power of 2 between 8 and 64 bytes. The block size must be a power of 2 between 128 and 4096 bytes.

According to the AHCI specification, each channel[k] controller uses a private *Command List* that is handled as a software FIFO. For each channel[k], the *Command List* can register up to 32 *read* or *write* commands, that are handled in pseudo-parallelism by the channel controller. This VCI component has a DMA capability, and use it to access both the *Command List* and to transfer the data to or from memory.

On the VCI side, it supports both 32 bits and 64 bits data words, and up to 64 bits address width.

For each channel, a single IRQ[k] can be (optionally) asserted as soon as at list one command in the Command List is completed. WARNING: the IRQ[k] is associated to a specific channel, but not to a specific command.

This hardware component checks for segmentation violation, and can be used as a default target.

2) Command List

For each channel, the VciMultiAhci driver must use two arrays to register commands: The Command Descriptor array (32 entries) define the Command List (software FIFO). Each Command Descriptor occupies 16 bytes, with the following format:

```
typedef struct hba_cmd_desc_s // size = 16 bytes
{
    unsigned char    flag[2];           // only one bit used : WRITE when bit 6 of flag[0] is set
    unsigned char    prdtl[2];          // Number of buffers (no more than 16535)
    unsigned int     prdbc;              // Number of bytes actually transferred
    unsigned int     ctba;               // Command Table base address 32 LSB bits
    unsigned int     ctbau;             // Command Table base address 32 MSB bits
} hba_cmd_desc_t;
```

3) Command Table

2) Addressable registers

Each channel[k] contains six 32 bits read/write registers:

- **HBA_PXCLB**

32 LSB bits of the Command List array physical address.

- **HBA_PXCLBU**

32 MSB bits of the Command List array physical address. *

- **HBA_PXIS**

Channel status, used for error reporting.

- **HBA_PXIE**

Intcommanderrupt enable.

- **HBA_PXCMD**

Boolean : running when non zero

- **HBA_PXCI**

Bit-vector, one bit per command in the Command List. These bits are handled as 32 set/reset flip-flops: set by software when a command has been posted in Command List / reset by hardware when the command is completed.

- **BLOCK_DEVICE_OP** (write only)

Type of operation, writing here initiates the operation. This register goes back to BLOCK_DEVICE_NOOP when operation is finished. The following operations codes are defined:

BLOCK_DEVICE_NOOP No operation
BLOCK_DEVICE_READ Transfer from block device to memory
BLOCK_DEVICE_WRITE Transfer from memory to block device

- **BLOCK_DEVICE_STATUS** (read only)

State of the transfer. Reading this register while not busy resets its value to IDLE, and acknowledge the IRQ. Value may be one of :

BLOCK_DEVICE_IDLE
BLOCK_DEVICE_BUSY
BLOCK_DEVICE_READ_SUCCESS
BLOCK_DEVICE_WRITE_SUCCESS
BLOCK_DEVICE_READ_ERROR
BLOCK_DEVICE_WRITE_ERROR

- **BLOCK_DEVICE_IRQ_ENABLE** (read/write)

Boolean enabling the IRQ line

- **BLOCK_DEVICE_SIZE** (read only)

Number of blocks addressable in the block device

- **BLOCK_DEVICE_BLOCK_SIZE** (read only)

Block size (in bytes)

For extensibility issues, you should access this component using globally-defined offsets. You should include file `soclib/block_device.h` from your software, it defines `BLOCK_DEVICE_COUNT`, `BLOCK_DEVICE_READ`, ...

Sample code: Please see reference implementation in source:trunk/soclib/soclib/platform/topcells/caba-vgmn-block_device-mips32el

(add `-I/path/to/soclib/include` to your compilation command-line)

2) Component definition & usage

source:trunk/soclib/soclib/module/connectivity_component/vci_block_device/caba/metadata/vci_block_device.sd?

See [SoclibCc/VciParameters](#)

```
Uses( 'vci_block_device', **vci_parameters )
```

3) CABA Implementation

CABA sources

- interface :
source:trunk/soclib/soclib/module/connectivity_component/vci_block_device/caba/source/include/vci_block_device.h
- implementation :
source:trunk/soclib/soclib/module/connectivity_component/vci_block_device/caba/source/src/vci_block_device.cpp?

CABA Constructor parameters

```
VciBlockDevice(  
    sc_module_name name,    // Component Name  
    const soclib::common::MappingTable &mt, // MappingTable  
    const soclib::common::IntTab &srcid,    // Initiator index  
    const soclib::common::IntTab &tgtid,    // Target index  
    const std::string &filename, // mapped file, may be a host block device  
    const uint32_t block_size = 512, // block size in bytes  
    const uint32_t latency = 0); // initial access time (number of cycles)
```

CABA Ports

- **p_resetrn** : Global system reset
- **p_clk** : Global system clock
- **p_vci_target** : The VCI target port
- **p_vci_initiator** : The VCI initiator port
- **p_irq** : Interrupt port

4) TLM-DT Implementation

TLM-DT sources

- interface :
source:trunk/soclib/soclib/module/connectivity_component/vci_block_device/tlmdt/source/include/vci_block_device.h
- implementation :

TLM-DT Constructor parameters

```
VciBlockDevice(  
    sc_module_name name,    // Component Name  
    const soclib::common::MappingTable &mt, // MappingTable  
    const soclib::common::IntTab &srcid,    // Initiator index  
    const soclib::common::IntTab &tgtid,    // Target index  
    const std::string &filename, // mapped file, may be a host block device  
    const uint32_t block_size = 512, // block size in bytes  
    const uint32_t latency = 0); // initial access time (number of cycles)
```

TLM-DT Ports

- **p_vci_target** : The VCI target port
- **p_vci_initiator** : The VCI initiator port
- **p_irq** : Interrupt port