

VciTimer

1) Functional Description

This VCI target is a memory mapped peripheral that can control up to 256 software controlled timers. Each timer can optionally generate an independent periodic interrupt. The memory segment allocated to this component must be aligned on 4K bytes boundary.

This hardware component checks for segmentation violation, and can be used as a default target.

The timer index *i* is defined by the ADDRESS[12:4] bits.

Each timer contains 4 memory mapped registers:

- `TIMER_VALUE`

This 32 bits register is unconditionally incremented at each cycle. A read request returns the current time contained in this register. A write request sets a new value in this register.

- `TIMER_MODE` This register contains two flags:
 - ◆ Bit 0: `TIMER_RUNNING`. When 1, the associated timer will decrease on each cycle
 - ◆ Bit 1: `TIMER_IRQ_ENABLED`: When 1, the associated IRQ line will be activated if the timer underflows.

- `TIMER_PERIOD`

This 32 bits register defines the period between two successive interrupts. It may be read or written to. When written to, the new period is immediately taken into account.

- `TIMER_RESETIRQ`

Any write request in this Boolean register will reset the pending IRQ. A read request returns the zero value when there is no pending interrupt, and returns a non zero value if there is a pending interrupt.

For extensibility issues, you should access your terminal using globally-defined offsets.

The file source:trunk/soclib/soclib/module/internal_component/vci_timer/include/soclib/timer.h defines `TIMER_VALUE`, `TIMER_MODE`, `TIMER_PERIOD`, `TIMER_RESETIRQ`, `TIMER_SPAN`, `TIMER_RUNNING`, `TIMER_IRQ_ENABLED`.

Sample code:

```
#include "soclib/timer.h"

static const volatile void* timer_address = 0xc0000000;

static timer_test(const size_t timer_no)
{
    // Getting / setting timer current value
    soclib_io_set( timer_address, TIMER_SPAN*timer_no + TIMER_VALUE, 0x2a00 );
    uint32_t foo = soclib_io_get( timer_address, TIMER_SPAN*timer_no + TIMER_VALUE );
}
```

```

// Enabling timer and interrupt
soclib_io_set( timer_address, TIMER_SPAN*timer_no + TIMER_MODE, TIMER_RUNNING | TIMER_IRQ_EN

// Getting IRQ status, and resetting IRQ
if ( soclib_io_get( timer_address, TIMER_SPAN*timer_no + TIMER_RESETIrq ) )
    soclib_io_set( timer_address, TIMER_SPAN*timer_no + TIMER_RESETIrq, 0 );
}

```

(add -I/path/to/soclib/include to your compilation command-line)

2) Component definition & usage

source:trunk/soclib/soclib/module/internal_component/vci_timer/caba/metadata/vci_timer.sd?

```
Uses( 'vci_timer' )
```

3) CABA Implementation

CABA sources

- interface :
source:trunk/soclib/soclib/module/internal_component/vci_timer/caba/source/include/vci_timer.h?
- implementation :
source:trunk/soclib/soclib/module/internal_component/vci_timer/caba/source/src/vci_timer.cpp?

CABA Constructor parameters

```

VciTimer(
    sc_module_name name,    // Component Name
    const soclib::common::IntTab & index, // Target index
    const soclib::common::MappingTable &mt, // MappingTable
    size_t nirq;           // Number of available timers

```

CABA Ports

- **p_resetrn** : Global system reset
- **p_clk** : Global system clock
- **p_vci** : VCI target port
- **p_irq[i]** : As many output IRQ ports as timers

4) TLM-DT Implementation

TLM-DT sources

- interface :
source:trunk/soclib/soclib/module/internal_component/vci_timer/tlmdt/source/include/vci_timer.h?
- implementation :
source:trunk/soclib/soclib/module/internal_component/vci_timer/tlmdt/source/src/vci_timer.cpp?

TLM-DT Constructor parameters

```

VciTimer(
    sc_module_name name,    // Component Name
    const soclib::common::IntTab & index, // Target index

```

```
const soclib::common::MappingTable &mt,    // MappingTable
size_t ntimer);    // Number of available timers
```

TLM-DT Ports

- **p_vci_target** *VCI target port*
- **p_irq_initiator[i]** *as many IRQ output ports as timers*