

VciRingInitiatorWrapper

1) Functional Description

This hardware component connects a VCI initiator to a RING interconnect. It can be used in conjunction with the [VciRingTargetWrapper](#) component to build a RING interconnect. This type of interconnect is well suited for FPGA implementations.

2) Component definition & usage

[source:trunk/soclib/soclib/module/network_component/vci_ring_initiator_wrapper/caba/metadata/vci_ring_initiator_wrapper](#)

3) CABA Implementation

CABA sources

- interface :
[source:trunk/soclib/soclib/module/network_component/vci_ring_initiator_wrapper/caba/source/include/vci_ring_initiator_wrapper.h](#)
- implementation :
[source:trunk/soclib/soclib/module/network_component/vci_ring_initiator_wrapper/caba/source/src/vci_ring_initiator_wrapper.cpp](#)

CABA Constructor parameters

```
VciRingInitiatorWrapper(sc_module_name insname,           // instance name
                        bool          alloc_init,          // default token owner
                        const int      &wrapper_fifo_depth, // command and response fifo
                        const soclib::common::MappingTable &mt, // mapping table
                        const soclib::common::IntTab &ringid, // Global subsystem index
                        const int &srcid);                 // attached initiator index
```

CABA Ports

- `sc_in<bool> p_clk;` *Global System Clock*
- `sc_in<bool> p_resetn;` *Global System reset*
- `soclib::caba::RingIn p_ring_in;` *Ring input port*
- `soclib::caba::RingOut p_ring_out;` *Ring output port*
- `soclib::caba::VciTarget<vci_param> p_vci;` *VCI target port*

4) TLM-T Implementation

The TLM-T implementation is not yet available.