

VciRingInitiatorWrapper

1) Functional Description

This hardware component connect a VCI initiator to a RING interconnect. It can be used in conjunction with the [VciRingTargetWrapper](#) component to build a RING interconnect. This type of interconnect is well suited for FPGA implementations.

2) Component definition & usage

[source:trunk/soclib/soclib/module/network_component/vci_ring_initiator_wrapper/caba/metadata/vci_ring_initiator_wrapper](#)

3) CABA Implementation

CABA sources

- interface :
[source:trunk/soclib/soclib/module/network_component/vci_ring_initiator_wrapper/caba/source/include/vci_ring_initiator_wrapper.h](#)
- implementation :
[source:trunk/soclib/soclib/module/network_component/vci_ring_initiator_wrapper/caba/source/src/vci_ring_initiator_wrapper.c](#)

CABA Constructor parameters

```
VciRingInitiatorWrapper(sc_module_name  insname,                // instance name
                        bool            alloc_init,              // default token owner
                        const int        &wrapper_fifo_depth,    // command and response fifo
                        const soclib::common::MappingTable &mt,    // mapping table
                        const soclib::common::IntTab &ringid,      // Global subsystem index
                        const int &srcid);                        // attached initiator index
```

CABA Ports

```
* sc_in<bool>          p_clk;          // Global System Clock
* sc_in<bool>          p_resetn;       // Global System reset
* soclib::caba::!RingIn p_ring_in;    // Ring input port
* soclib::caba::!RingOut p_ring_out;  // Ring output port
* soclib::caba::!VciTarget<vci_param> p_vci; // VCI target port
```

4) TLM-T Implementation

The TLM-T implementation is not yet available.